

For residential segment

Gateway for  
quick installation

Data transfer to the  
Solar-Log WEB Enerest™

Small and compact design  
for DIN rail mounting



Article number

Solar-Log 50

256200

# Solar-Log 50

## The Gateway

---

### Function

#### Software Licenses

There are numerous add-on functions for the Gateway that can be enabled by purchasing the respective licenses from the portal ([license.solar-log.com](https://license.solar-log.com)). To enable this, the Solar-Log 50 has to be connected to the Internet.

### Display Options

#### Solar-Log WEB Enerest™

The new Solar-Log 50 acts as a Gateway between the PV plant and the Solar-Log WEB Enerest™ portal. Get your Solar-Log 50, including two years of Solar-Log WEB Enerest™ monitoring.

#### The App for End-Customers - Solar-Log WEB Enerest™

This app offers users comfort and security with its structured operating concept, intuitive controls, modern features and interactive graphics. The app is available for free from the app store.

### Connections

#### Inverters

The Gateway Solar-Log 50 is compatible with inverters from all the major manufacturers.

#### 2 x RS485 or 1 x RS422

To connect components.

#### Solar-Log™ USB Connection and Data Export

A USB stick can be connected for safe and quick manual installations of new firmware updates, configurations, and backups. The backup and configuration can be exported as a file via USB.

#### Ethernet

The Gateway Solar-Log 50 can be connected directly to compatible inverters via Ethernet.

## Technical Data

## Solar-Log 50

Basic Functions	Inverter and battery storage	Ethernet RS485 (4 pole) or RS422 <sup>1)</sup> (6 pole)
	Meter	RS485 (2 pole)
	Maximum number of components	5
	Maximum plant size	15 kWp
	Recommended cable length <sup>2)</sup>	30 m
Expandable Licenses <sup>3)</sup>	Solar-Log 50 Opening License for Feed-in Management	●
	Solar-Log 50 Opening License for the expansion up to 10 components	from 5 to maximum 10
	Solar-Log 50 Opening License for the plant expansion up to 30 kWp	from 15 kWp to maximum 30 kWp
Interfaces	RS485/RS422	2 x RS485 or 1 x RS422
	Ethernet	●
	USB connection	●
General Data	Power supply voltage and device voltage	24 V
	Connection to Solar-Log WEB Enerest™ (Internet connection required)	●
	Multi-lingual (DE, EN, ES, FR, IT, CN)	●
	Dimensions (w x h x d) in mm	53.6 x 89.7 x 35.5
	Warranty	2 years

## Solar-Log WEB Enerest™

MPP-Tracker monitoring / Number of MPP trackers depends on the inverter type	●
Inverter failure, status of fault and power monitoring	●
Yield forecast	●
Self-produced energy consumption: digital electricity meter	●

1) No RS485 meter connectable.

2) Depending on the inverter used and the cable type (details can also vary from one type of device to another).

3) With additional costs.



No power supply included

Components	Article number	Solar-Log 50	
Solar-Log™ PRO380-Mod	255913	●	Meters
Solar-Log™ PRO380-Mod-CT	256059	●	
Wireless Kit TP-Link	256012	●	WiFi
Wireless Kit Netgear	256013	●	
PowerLine Paket	256133	●	Misc.
Special PiggyBack for SMA	220020	●	

### Article Number

Solar-Log 50	256200
Power supply	256226
Mounting rail power supply	256227
Solar-Log 50 Opening License up to 30 kWp	256206
Solar-Log 50 Opening License up to 10 components	256205
Solar-Log 50 Opening License for Feed-in Management	256204
Solar-Log 50 multi purpose license*	256228

\* The multi-function license includes the three individual Solar-Log 50 licenses: article number 256204, 256205 and 256206.



[Installation on DIN rail mounting](#)

[Configuration Assistant](#)

[Setup in the Solar-Log WEB Enerest™](#)

[Buy and install license](#)